

MODEL		WEIGHT		ALLOWABLE TORQUE [kgf · m / Nm]	ALLOWABLE THRUST [ton / kN]	ALLOWABLE STEM DIA		MOUNTING FLANGE SIZE				
		BASIC [kg]	INTEGRAL [kg]			BORE & KEY [mm]	THREADED [mm]	ISO NO	FLANGE O.D [mm]	TAP PCD [mm]	TAP SIZE [mm]	PILOT DIA [mm]
TM-01	0.2	34	41	15 / 147	7 / 68.6	34	40	F 10	125	102	4×M10	70
	0.4	35	42									
	0.75	39(39)	46(46)									
	1.5	-44	-51									
TM-04	0.4	54	61	56 / 548.8	13 / 127.4	50	58	F 14	175	140	4×M16	100
	0.75	58	65									
	1.5	64	71									
	2.2	67 (67)	74 (74)									
	3.7	-73	-80									
TM-07	1.5	91	98	86 / 842.8	16 / 156.8	60	72	F 16	210	165	4×M20	130
	2.2	95	102									
	3.7	110	120									
	5.5	114(115)	124(125)									
	7.5	-122	-132									
TM-1	2.2	132	142	184 / 1803.2	27 / 264.6	80	95	F 25	300	254	8×M16	200
	3.7	146	156									
	5.5	150	161									
	7.5	162(158)	173(169)									
	11	-181	-192									
TM-3	5.5	340	355	400 / 3920	40 / 392	100	115	F 30	350	298	8×M20	230
	7.5	355	370									
	11	370	385									
	15	415	430									
	18.5	-415	-430									
TM-6	11	610	630	800 / 7840	68 / 666	140	160	F 35	415	356	8×M30	260
	15	620	640									
	18.5	660	680									
	22	660	680									
TM-12	18.5	1140	1160	1600 / 15680	122 / 1195	155	180	F 40	475	406	8×M36	300
	22	1140	1160									
	30	1180	1200									
	37	1180	1200									